



STEAM GENERATORS

NEW

SG-55

PRESSURE

8
bar

STEAM FLOW RATE

250
g/min

ABSORBED POWER

10,4
kW



EXCLUSIVE CHARACTERISTICS

- ▶ POWER BOIL
- ▶ ANTI BUGS
- ▶ POWER FILTER
- ▶ AUTOMATIC SHUTDOWN
- ▶ SAFETY
- ▶ ERGONOMICS
- ▶ POWER FLEX
- ▶ DURABILITY

MOST FREQUENTLY USE

AUTOMOTIVE



HO.RE.CA.



FOOD INDUSTRY AND RETAILERS



LARGE COMMON AREAS



SPECS



STANDARD VACUUM CLEANER IN STAINLESS STEEL STRUCTURE.



STAINLESS STEEL STRUCTURE



CONTROL PANEL:
- PRESSURE GAUGE
- BOILER TEMPERATURE DIGITAL INDICATOR
- STEAM READY INDICATOR LIGHT
- DETERGENT LACK INDICATOR LIGHT
- POWER SUPPLY INDICATOR LIGHT
- STEAM OUTPUT REGULATOR
- BOILER SWITCH
- DETERGENT SWITCH
- MAIN SWITCH

TECHNICAL DATA

		SG-55 8025 T
Code		GNVA40047
PERFORMANCE		
Operating pressure	bar/Mpa	8/0,8
Steam flow rate	g/min	250
Steam temperature (max)	°C	180
Start up time	min	~ 5
Power supply	Ph-V-Hz	3-400-50
Absorbed power max.	kW	10,4
Vacuum power	kW	1,4
Boiler volume	l	4,2
Water tank	l	15
Detergent tank	l	5
Dimension (LxWxH)	Cm	80x55x102
Weight	Kg	47

STANDARD EQUIPMENT

CODE: IPIP40021
HANDGRIP + HOSE 4 m



CODE: MPVR40958
HOSE EXTENSION
L=500 mm 2 PZ



CODE: SPPV40060
MULTIPURPOSE FLOOR
BRUSH



CODE: SPPV40061
CARPET PROTECTION FOR
MULTIPURPOSE BRUSH



CODE: SPPV40062
FRAME WITH BRISTLES AND
RUBBER SCRAPERS FOR
MULTIPURPOSE BRUSH



CODE: SPPV40063
GLASS CLEANER



CODE: SPPV40064
PROFESSIONAL
TRANSPARENT NOZZLE



CODE: SPPV40065
LARGE SUCTION NOZZLE
+ SQUEEGEE



CODE: SPPV40066
SMALL SUCTION NOZZLE



CODE: SPPV40067
STEAM LANCE



CODE: SPPV40056
ROUND BRUSH POLYESTER
BRISTLE Ø28 mm



CODE: SPPV40068
ROUND BRUSH POLYESTER
BRISTLE Ø65 mm



CODE: SPPV40069
ROUND BRUSH POLYESTER
BRISTLE Ø40 mm



CODE: SPPV40070
ROUND BRUSH INOX
BRISTLE Ø40 mm



CODE: AZMC40024
WRENCH FOR
MAINTENANCE

